## NSN 5306-00-115-9421

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-115-9421 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.626 inches and 0.686 inches **Fastener Length:** 1.438 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.752 inches and 0.812 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches grip Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

## **NSN 5306-00-115-9421**Machine Bolt - Page 2 of 2



		eas	

Demilitarization:

No

Fiig:

A003b0