NSN 5306-00-116-1422

Machine Bolt - Page 1 of 2

Thread Class:

За



View Online at https://aerobasegroup.com/nsn/5306-00-116-1422

| Thread Direction: |
|---|
| Right-hand |
| Thread Length: |
| Between 0.589 inches and 0.609 inches |
| Fastener Length: |
| 0.688 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.330 inches |
| Width Between Flats: |
| Between 0.305 inches and 0.313 inches |
| Extended Washer Diameter: |
| 0.438 inches |
| Extended Washer Thickness: |
| Between 0.060 inches and 0.070 inches |
| Hole Diameter: |
| 0.070 inches |
| Thread Diameter: |
| 0.250 inches |
| Grip Length: |
| Between 0.079 inches and 0.099 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Features Provided: |
| Finished head |
| Thready Qty Per Inch (tpi): |
| 28 |
| Hardness Rating: |
| 42.0 rockwell c and 46.0 rockwell c |
| Hole Configuration Style: |
| Round longitudinal hole |
| Surface Finish: |
| 32.0 microinches threads |
| Material: |
| Steel comp 601 |
| Material Specification: |
| Ams 6304 assn standard single material response |
| |

NSN 5306-00-116-1422 Machine Bolt - Page 2 of 2

Fiig: A003b0



| Surface Treatment: |
|--|
| Nickel and cadmium |
| Surface Treatment Specification: |
| Ams 2416 assn standard single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |