# NSN 5306-00-116-1426

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-116-1426



**Thread Class:** 

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.339 inches and 0.359 inches

## Fastener Length:

0.438 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.300 inches

Width Between Flats:

Between 0.305 inches and 0.313 inches

#### **Extended Washer Diameter:**

0.438 inches

#### **Extended Washer Thickness:**

Between 0.060 inches and 0.070 inches

Hole Diameter:

0.070 inches

**Thread Diameter:** 

0.250 inches

Grip Length:

Between 0.079 inches and 0.099 inches

## Hole Quantity:

4

Hole Type:

Drilled

**Features Provided:** 

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

130000 pounds per square inch

Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

Minimum Yield Strength:

85000 pounds per square inch

Hole Configuration Style:

Double hexagon longitudinal hole

Surface Finish:

32.0 microinches threads

# NSN 5306-00-116-1426

Machine Bolt - Page 2 of 2



Material:

Iron alloy 660

## Material Specification:

Ams 5731 assn standard single material response

### **Precious Material:**

Silver

# Surface Treatment:

Silver

# Surface Treatment Specification:

Ams 2410 assn standard single treatment response

### **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

#### Unit Of Measure:

--

## Demilitarization:

No

## Fiig:

A003b0