

View Online at <https://aerobasegroup.com/nsn/5306-00-116-1795>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.433 inches and 0.478 inches

**Fastener Length:**

Between 1.577 inches and 1.607 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.203 inches and 0.235 inches

**Width Between Flats:**

0.562 inches

**Shoulder Diameter:**

0.4360 inches first shoulder and 0.4370 inches first shoulder

**Shoulder Length:**

1.129 inches first shoulder and 1.144 inches first shoulder

**Thread Diameter:**

0.375 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Shoulder Shape:**

Round first shoulder

**Material:**

Steel

**Material Specification:**

Mil-s-5000, cond c military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

13101, type 1, cl c fscm 76301 mfr ref single treatment response

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5000 spec.