## NSN 5306-00-116-4083

Shoulder Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-116-4083 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.760 inches **Fastener Length:** 2.240 inches **Head Style:** Hexagon **Head Height:** 0.280 inches Width Between Flats: Between 0.612 inches and 0.625 inches **Shoulder Diameter:** 0.4340 inches first shoulder and 0.4360 inches first shoulder **Shoulder Length:** 0.640 inches first shoulder and 0.660 inches first shoulder **Thread Diameter:** 0.312 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 150000 pounds per square inch Hardness Rating: 32.0 rockwell c and 38.0 rockwell c **Shoulder Shape:** Round first shoulder Material: Steel **Material Specification:** Sae j429 gr 8 assn standard single material response **Surface Treatment:** Phosphate **Surface Treatment Specification:** Mil-c-16232, type 2 military specification single treatment response **Thread Series Designator:** Unf Shelf Life:

**Unit Of Measure:** 

N/a

## NSN 5306-00-116-4083

Shoulder Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-16232 spec.