NSN 5306-00-116-6667

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-116-6667 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.469 inches **Fastener Length:** Between 1.570 inches and 1.610 inches **Head Style:** Hexagon **Head Height:** Between 0.172 inches and 0.190 inches Width Between Flats: Between 0.367 inches and 0.375 inches **First Diameter From Head:** Between 0.248 inches and 0.249 inches **Second Diameter From Head:** Between 0.213 inches and 0.216 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.850 inches and 0.890 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.121 inches **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 Hardness Rating: 28.0 rockwell c and 34.0 rockwell c **Askewed Head Angle:** Between 88.0 degrees and 92.0 degrees **Externally Relieved Body Diameter Quantity:** Material: Steel comp 8640 or steel comp 4140 or steel comp 8740 **Material Specification:** Sae j404 assn standard all material responses **Surface Treatment:** Oxide **Thread Series Designator:** Unc Shelf Life:

N/a

NSN 5306-00-116-6667

Externally Relieved Body Bolt - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0