NSN 5306-00-118-6202

View Online at https://aerobasegroup.com/nsn/5306-00-118-6202

Shoulder Bolt - Page 1 of 2



Thread Class: За **Thread Direction:** Right-hand Thread Length: Between 0.390 inches and 0.450 inches **Fastener Length:** Between 0.830 inches and 0.850 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.365 inches and 0.385 inches Width Between Flats: Between 0.367 inches and 0.376 inches **Extended Washer Diameter:** Between 0.490 inches and 0.510 inches **Extended Washer Thickness:** Between 0.070 inches and 0.080 inches **Shoulder Diameter:** 0.3000 inches and 0.3005 inches first shoulder **Shoulder Length:** 0.348 inches and 0.368 inches first shoulder **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 28 **Shoulder Shape:** Round first shoulder **Product Name:** Navy special project Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Pwa 830 fscm 77445 mfr ref single treatment response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-00-118-6202 Shoulder Bolt - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

Demilitarization:

No

Fiig:

A003b0