## NSN 5306-00-119-1988

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-119-1988 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.400 inches and 0.450 inches Fastener Length: Between 0.910 inches and 0.940 inches **Head Style:** Dished hexagon **Head Height:** Between 0.125 inches and 0.140 inches Width Between Flats: Between 0.430 inches and 0.439 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.490 inches and 0.510 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch Material: Iron alloy 660 **Material Specification:** Ams 5732 assn standard single material response **Surface Treatment: Passivate** Surface Treatment Specification esponse

Surface Treatment Specification:
Mil-s-5002 military specification single treatment re
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0

## NSN 5306-00-119-1988

Shear Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-s-5002 spec.