

View Online at <https://aerobasegroup.com/nsn/5306-00-119-4700>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.242 inches and 0.392 inches

Fastener Length:

Between 1.710 inches and 1.757 inches

Head Style:

Double hexagon

Head Height:

Between 0.177 inches and 0.197 inches

Width Between Flats:

Between 0.492 inches and 0.502 inches

Grip Diameter:

Between 0.3100 inches and 0.3110 inches

Shank Unthreaded Hole Diameter:

0.066 inches first hole and 0.086 inches first hole

Thread Diameter:

0.312 inches

Grip Length:

Between 1.365 inches and 1.385 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

200000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 49.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.497 inches first hole and 1.517 inches first hole

Material:

Steel

Material Specification:

Aics-501 fscm 06725 mfr ref single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

56878-ewsb22 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0