## NSN 5306-00-121-2672

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-121-2672 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.531 inches **Fastener Length:** 1.031 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Grip Diameter:** Between 0.1894 inches and 0.1899 inches **Thread Diameter:** 0.192 inches **Grip Length:** 0.500 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

## NSN 5306-00-121-2672

Close Tolerance Bolt - Page 2 of 2



		eas	

--

Demilitarization:

No

Fiig:

A003b0