# NSN 5306-00-121-2677

Machine Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-121-2677

#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.630 inches and 0.690 inches

#### Fastener Length:

1.125 inches

#### Head Style:

Double hexagon w/hole

#### **Head Height:**

0.260 inches

#### Width Between Flats:

Between 0.243 inches and 0.251 inches

#### **Extended Washer Diameter:**

0.375 inches

#### **Extended Washer Thickness:**

Between 0.040 inches and 0.050 inches

#### Thread Diameter:

0.190 inches

# Grip Length:

Between 0.435 inches and 0.495 inches

#### **Features Provided:**

Finished head

#### Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

130000 pounds per square inch

#### Hardness Rating:

248.0 brinell standard and 341.0 brinell standard

#### Minimum Yield Strength:

85000 pounds per square inch

#### Surface Finish:

32.0 microinches threads

#### Material:

Iron alloy 660

#### **Material Specification:**

Ams 5731 assn standard single material response

# **Thread Series Designator:**

Unjf

# Shelf Life:

N/a



# NSN 5306-00-121-2677

Machine Bolt - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

