## NSN 5306-00-121-7855

Machine Bolt - Page 1 of 2

**Thread Class:** 

За



View Online at https://aerobasegroup.com/nsn/5306-00-121-7855

Right-hand Thread Length: Between 0.630 inches and 0.690 inches Fastener Length: 1.562 inches Head Style: Double hexagon w/hole Head Height: 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Between 0.630 inches and 0.690 inches  Fastener Length: 1.562 inches  Head Style: Double hexagon w/hole  Head Height: 0.260 inches  Width Between Flats: Between 0.243 inches and 0.251 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Hole Diameter: 0.047 inches  Thread Diameter: 0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
Fastener Length: 1.562 inches Head Style: Double hexagon w/hole Head Height: 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Head Style: Double hexagon w/hole Head Height: 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Head Style: Double hexagon w/hole Head Height: 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Double hexagon w/hole  Head Height:  0.260 inches  Width Between Flats:  Between 0.243 inches and 0.251 inches  Extended Washer Diameter:  0.375 inches  Extended Washer Thickness:  Between 0.040 inches and 0.050 inches  Hole Diameter:  0.047 inches  Thread Diameter:  0.190 inches  Grip Length:  Between 0.872 inches and 0.932 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  130000 pounds per square inch
Head Height: 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Width Between Flats: Between 0.243 inches and 0.251 inches Extended Washer Diameter: 0.375 inches Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Between 0.243 inches and 0.251 inches  Extended Washer Diameter: 0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Hole Diameter: 0.047 inches  Thread Diameter: 0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
Extended Washer Diameter:  0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Hole Diameter:  0.047 inches  Thread Diameter:  0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity:  4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  130000 pounds per square inch
0.375 inches  Extended Washer Thickness: Between 0.040 inches and 0.050 inches  Hole Diameter: 0.047 inches  Thread Diameter: 0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled  Features Provided: Finished head  Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
Extended Washer Thickness: Between 0.040 inches and 0.050 inches Hole Diameter: 0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Between 0.040 inches and 0.050 inches  Hole Diameter:  0.047 inches  Thread Diameter:  0.190 inches  Grip Length:  Between 0.872 inches and 0.932 inches  Hole Quantity:  4  Hole Type:  Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  130000 pounds per square inch
Hole Diameter:  0.047 inches Thread Diameter:  0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity:  4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
0.047 inches Thread Diameter: 0.190 inches Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Thread Diameter:  0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
0.190 inches  Grip Length: Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
Grip Length: Between 0.872 inches and 0.932 inches Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Between 0.872 inches and 0.932 inches  Hole Quantity: 4  Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32  Min. Tensile Strength (psi): 130000 pounds per square inch
Hole Quantity: 4 Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Hole Type: Drilled Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Drilled  Features Provided:  Finished head  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  130000 pounds per square inch
Features Provided: Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
Finished head  Thready Qty Per Inch (tpi):  32  Min. Tensile Strength (psi):  130000 pounds per square inch
Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch
32  Min. Tensile Strength (psi): 130000 pounds per square inch
Min. Tensile Strength (psi): 130000 pounds per square inch
130000 pounds per square inch
Hardness Rating:
248.0 brinell standard and 341.0 brinell standard
Minimum Yield Strength:
95000 poundo por equero inch
85000 pounds per square inch
Hole Configuration Style:

32.0 microinches threads

## NSN 5306-00-121-7855

Machine Bolt - Page 2 of 2



Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response
Precious Material:
Silver
Surface Treatment:
Silver
Surface Treatment Specification:
Ams 2410 assn standard single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0