NSN 5306-00-121-8182

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/psn/5306-00-121-8182

View Online at https://aerobasegroup.com/nsn/5306-00-121-8182
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.901 inches and 0.951 inches
Fastener Length:
Between 3.161 inches and 3.191 inches
Head Style:
Double hexagon w/hole
Head Height:
0.530 inches
Width Between Flats:
Between 0.616 inches and 0.627 inches
Extended Washer Diameter:
Between 0.940 inches and 0.950 inches
Extended Washer Thickness:
0.098 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.240 inches and 2.260 inches
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837 type 1 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Shelf Life:
N/a

NSN 5306-00-121-8182

Shear Bolt - Page 2 of 2



U	n	it	Of	Μe	eas	ur	e:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-8837 spec.