

View Online at <https://aerobasegroup.com/nsn/5306-00-121-8901>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.236 inches and 0.318 inches

**Fastener Length:**

Between 1.122 inches and 1.142 inches

**Head Style:**

Dished hexagon

**Head Height:**

Between 0.095 inches and 0.110 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Grip Diameter:**

Between 0.1885 inches and 0.1894 inches

**Shank Unthreaded Hole Diameter:**

0.070 inches first hole and 0.080 inches first hole

**Thread Diameter:**

0.190 inches

**Grip Length:**

Between 0.750 inches and 0.766 inches

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

36.0 rockwell c and 41.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.029 inches first hole and 1.059 inches first hole

**Surface Finish:**

63.0 microinches grip

**Special Features:**

W/retaining element on shank

**Material:**

Steel

**Material Specification:**

Mil-b-83050 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 2 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-b-83050 spec.