NSN 5306-00-123-8532

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-123-8532 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.630 inches and 0.690 inches **Fastener Length:** 1.375 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.685 inches and 0.745 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

NSN 5306-00-123-8532 Machine Bolt - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

Demilitarization:

No

Fiig:

A003b0