## NSN 5306-00-124-3023

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-124-3023 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.750 inches and 0.810 inches **Fastener Length:** 1.750 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.300 inches Width Between Flats: Between 0.305 inches and 0.313 inches **Extended Washer Diameter:** 0.438 inches **Extended Washer Thickness:** Between 0.060 inches and 0.070 inches **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.940 inches and 1.000 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 130000 pounds per square inch **Hardness Rating:** 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response **Thread Series Designator:** Unjf Shelf Life:

N/a

## **NSN 5306-00-124-3023** Machine Bolt - Page 2 of 2



	• •						
ın	18	Of	ΝЛ	ດລ	CI.	ır	ο.

Demilitarization:

No

Fiig:

A003b0