## NSN 5306-00-126-5150

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-126-5150 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.669 inches and 0.719 inches **Fastener Length:** Between 3.679 inches and 3.709 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.425 inches and 0.445 inches Width Between Flats: Between 0.492 inches and 0.502 inches **Extended Washer Diameter:** Between 0.740 inches and 0.750 inches **Extended Washer Thickness:** Between 0.089 inches and 0.109 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **End Application:** Sea knight helicopter **Thread Diameter:** 0.438 inches **Grip Length:** Between 2.990 inches and 3.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** 

Unjf

Shelf Life:

N/a

## NSN 5306-00-126-5150

Shear Bolt - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.