NSN 5306-00-126-5151

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-126-5151 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 1.562 inches and 1.612 inches **Fastener Length:** Between 6.072 inches and 6.102 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 1.041 inches and 1.061 inches Width Between Flats: Between 1.239 inches and 1.252 inches **Extended Washer Diameter:** Between 1.865 inches and 1.875 inches **Extended Washer Thickness:** Between 0.248 inches and 0.268 inches **Grip Diameter:** Between 1.1225 inches and 1.1240 inches **Thread Diameter:** 1.125 inches **Grip Length:** Between 4.490 inches and 4.510 inches Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 180000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a

--

Unit Of Measure:

NSN 5306-00-126-5151

Shear Bolt - Page 2 of 2



Demi			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.