## NSN 5306-00-127-7230



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-127-7230 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.374 inches and 0.453 inches **Fastener Length:** Between 4.265 inches and 4.312 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 3.859 inches and 3.891 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 62000 pounds per square inch Material: Aluminum alloy **Material Specification:** Qq-a-200 federal specification single material response or qq-a-430 federal specification single material response or qq-a-225 federal specification single material response **Surface Treatment:** Oxide film and anodize **Surface Treatment Specification:** Mil-c-5541 military specification 1st treatment response and mil-a-8625 military specification 2nd treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

**Demilitarization:** No

Fiig:

A003b0

## NSN 5306-00-127-7230

Machine Bolt - Page 2 of 2



Mil-std (military Standard):

Mil-c-5541 spec.