NSN 5306-00-127-7353

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-127-7353

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.901 inches and 0.951 inches
Fastener Length:
Between 3.036 inches and 3.066 inches
Head Style:
Double hexagon w/hole
Head Height:
0.530 inches
Width Between Flats:
Between 0.610 inches and 0.625 inches
Extended Washer Diameter:
Between 0.940 inches and 0.950 inches
Extended Washer Thickness:
0.098 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.4985 inches and 0.4995 inches
Thread Diameter:
0.500 inches
Grip Length:
Between 2.115 inches and 2.135 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
20
Min. Tensile Strength (psi):
260000 pounds per square inch
Hardness Rating:
51.0 rockwell c and 54.0 rockwell c
Hole Configuration Style:
Round
Material:
Steel comp h11
Material Specification:
Ams 6485 assn standard single material response or ams6487 assn standard single material response

NSN 5306-00-127-7353

Shear Bolt - Page 2 of 2

Mil-c-8837 spec.



Surface Treatment:
Cadmium
Surface Treatment Specification:
Mil-c-8837 type 1 cl 2 military specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
56878-ewb26 manufacturers standard
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):