NSN 5306-00-128-1509

Internally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-128-1509

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.361 inches
Fastener Length:
0.561 inches
Head Style:
Hexagon extended washer
Head Height:
0.439 inches
Width Between Flats:
0.750 inches
Extended Washer Diameter:
1.000 inches
Extended Washer Thickness:
0.150 inches
Concentric Hole Depth:
0.900 inches
Counterbore Diameter:
Between 0.402 inches and 0.410 inches
Counterbore Depth:
0.350 inches
Concentric Hole Diameter:
Between 0.164 inches and 0.171 inches
Thread Diameter:
0.750 inches
Thready Qty Per Inch (tpi):
16
Special Features:
Externally relieved to 0.650 in. 1st diameter from head by 0.200 in. Largest bearing surface of head to end of 1st dia
Material:
Aluminum alloy 2024
Material Specification:
Qq-a-225/6 federal specification single material response
Surface Treatment:
Anodize
Surface Treatment Specification:
Mil-a-8625 type 1 military specification single treatment response
Style Designator:

Counterbore unthreaded

NSN 5306-00-128-1509

Internally Relieved Body Bolt - Page 2 of 2



Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0
Mil-std (military Standard):

Mil-a-8625 spec.