NSN 5306-00-130-7655

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-130-7655

view Online at https://aerobasegroup.com/nsn/5306-00-130-7655
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.547 inches and 0.597 inches
Fastener Length:
Between 0.807 inches and 0.837 inches
Head Style:
Double hexagon w/hole
Head Height:
Between 0.338 inches and 0.358 inches
Width Between Flats:
Between 0.368 inches and 0.377 inches
Extended Washer Diameter:
Between 0.521 inches and 0.531 inches
Extended Washer Thickness:
Between 0.072 inches and 0.092 inches
Hole Diameter:
0.055 inches
Grip Diameter:
Between 0.3110 inches and 0.3120 inches
Thread Diameter:
0.312 inches
Grip Length:
Between 0.240 inches and 0.260 inches
Hole Quantity:
4
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Hole Configuration Style:
Round
Material:
Titanium alloy
Material Specification:
Nas 621 comp 6al-4v assn standard single material response
Thread Series Designator:
Unf

Unf

NSN 5306-00-130-7655

Shear Bolt - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0