NSN 5306-00-131-2599

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-131-2599 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.560 inches **Fastener Length:** 2.270 inches **Head Style:** Dee **Head Diameter:** Between 0.620 inches and 0.630 inches **Head Height:** 0.190 inches **Distance From Centerline To Flat:** Between 0.240 inches and 0.250 inches First Diameter From Head: Between 0.316 inches and 0.321 inches **Second Diameter From Head:** Between 0.3805 inches and 0.3810 inches **Third Diameter From Head:** Between 0.3695 inches and 0.3735 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.630 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 1.094 inches and 1.157 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: Between 1.469 inches and 1.595 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): **Hardness Rating:** 30.0 rockwell c and 34.0 rockwell c **Externally Relieved Body Diameter Quantity: Special Features:** Thd point flatted to 0.260 in. W by 0.160 in. Lg, top of head partially beveled to 30.0 deg Material: Steel comp 8740

Unf

Thread Series Designator:

NSN 5306-00-131-2599

Externally Relieved Body Bolt - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0