

View Online at <https://aerobasegroup.com/nsn/5306-00-131-7290>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.532 inches

**Eye Inside Diameter:**

Between 0.313 inches and 0.316 inches

**Shoulder Thickness:**

0.094 inches

**Shank Length:**

1.844 inches

**Eye Stock Thickness:**

0.188 inches

**Shoulder Diameter:**

Between 0.313 inches and 0.316 inches

**Shank Unthreaded Hole Diameter:**

0.076 inches first hole

**Ring Stock Diameter:**

0.250 inches

**Ring Inside Diameter:**

1.250 inches

**Overall Length:**

2.876 inches

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

150000 pounds per square inch

**Hardness Rating:**

34.0 rockwell c and 38.0 rockwell c

**Distance From Center Of Eye To Shank End:**

2.438 inches

**Material:**

Steel comp 4130

**Material Specification:**

Mil-s-6758 military specification single material response

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 2 federal specification all treatment responses

**Style Designator:**

Round, closed w/shoulder

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-s-6758 spec.