

View Online at <https://aerobasegroup.com/nsn/5306-00-131-7290>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.532 inches

Eye Inside Diameter:

Between 0.313 inches and 0.316 inches

Shoulder Thickness:

0.094 inches

Shank Length:

1.844 inches

Eye Stock Thickness:

0.188 inches

Shoulder Diameter:

Between 0.313 inches and 0.316 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole

Ring Stock Diameter:

0.250 inches

Ring Inside Diameter:

1.250 inches

Overall Length:

2.876 inches

Thread Diameter:

0.312 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

34.0 rockwell c and 38.0 rockwell c

Distance From Center Of Eye To Shank End:

2.438 inches

Material:

Steel comp 4130

Material Specification:

Mil-s-6758 military specification single material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2, cl 2 federal specification all treatment responses

Style Designator:

Round, closed w/shoulder

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-6758 spec.