NSN 5306-00-135-0656

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-135-0656 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.250 inches **Fastener Length:** 12.250 inches **Head Style:** Pan no. 2 **Head Diameter:** 1.375 inches **Head Height:** 0.625 inches **Shank Unthreaded Hole Diameter:** 4.2 millimeters first hole First Diameter From Head: Between 0.714 inches and 0.724 inches **Second Diameter From Head:** 0.938 inches **Third Diameter From Head:** Between 0.714 inches and 0.724 inches **Fourth Diameter From Head:** 0.938 inches Fifth Diameter From Head: Between 0.714 inches and 0.724 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.438 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 2.688 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 3.500 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 4.500 inches Distance From Largest Bearing Surface Of Head To End Of Fifth Diameter: 6.250 inches **Thread Diameter:** 0.875 inches Thready Qty Per Inch (tpi):

0.750 inches

Tenth Diameter From Head:

NSN 5306-00-135-0656

Externally Relieved Body Bolt - Page 2 of 2



| Eighth Diameter From Head: |
|---|
| 0.938 inches |
| Distance From Largest Bearing Surface Of Head To End Of Seventh Diameter: |
| 8.125 inches |
| Distance From Head Largest Bearing Surface To Shank Hole Center: |
| 12.031 inches first hole |
| Ninth Diameter From Head: |
| Between 0.714 inches and 0.724 inches |
| Externally Relieved Body Diameter Quantity: |
| 10 |
| Distance From Largest Bearing Surface Of Head To End Of Ninth Diameter: |
| 10.625 inches |
| Distance From Largest Bearing Surface Of Head To End Of Sixth Diameter: |
| 7.250 inches |
| Seventh Diameter From Head: |
| Between 0.714 inches and 0.724 inches |
| Sixth Diameter From Head: |
| 0.938 inches |
| Distance From Largest Bearing Surface Of Head To End Of Eighth Diameter: |
| 9.313 inches |
| Distance From Largest Bearing Surface Of Head To End Of Tenth Diameter: |
| 11.000 inches |
| Product Name: |
| Navy special project |
| Surface Treatment: |
| Phosphate |
| Thread Series Designator: |
| Unf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |