

View Online at <https://aerobasegroup.com/nsn/5306-00-135-7189>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.391 inches

**Fastener Length:**

Between 3.693 inches and 3.734 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.183 inches and 0.203 inches

**Width Between Flats:**

Between 0.552 inches and 0.564 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 3.302 inches and 3.322 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

180000 pounds per square inch

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

3.573 inches first hole and 3.614 inches first hole

**Material:**

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2 cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unjf

**Specification Data:**

76823-51b464 manufacturers standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0