

View Online at <https://aerobasegroup.com/nsn/5306-00-136-1487>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.985 inches and 1.015 inches

Fastener Length:

Between 4.735 inches and 4.765 inches

Head Style:

Hexagon

Head Height:

0.125 inches

Width Between Flats:

0.439 inches

Hole Diameter:

0.046 inches

Locking Feature:

Strip threads

Grip Diameter:

0.2490 inches

Thread Diameter:

0.250 inches

Grip Length:

3.750 inches

Hole Quantity:

1

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

160000 pounds per square inch

Hole Configuration Style:

Hexagon flats

Material:

Steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5000 military specification 1st material response or mil-s-6049 military specification 2nd material response

Surface Treatment:

Nickel and cadmium

Surface Treatment Specification:

Ams 2416 assn standard all treatment responses

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5000 spec.