

View Online at <https://aerobasegroup.com/nsn/5306-00-138-0127>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.984 inches and 1.034 inches

Fastener Length:

Between 2.619 inches and 2.649 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.701 inches and 0.721 inches

Width Between Flats:

Between 0.803 inches and 0.814 inches

Extended Washer Diameter:

Between 1.220 inches and 1.230 inches

Extended Washer Thickness:

Between 0.168 inches and 0.188 inches

Grip Diameter:

Between 0.7480 inches and 0.7490 inches

Thread Diameter:

0.750 inches

Grip Length:

Between 1.615 inches and 1.635 inches

Thready Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

220000 pounds per square inch

Hardness Rating:

46.0 rockwell c and 50.0 rockwell c

Material:

Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

56878-lwb22 manufacturers standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0