NSN 5306-00-138-4310

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-138-4310 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.309 inches and 0.359 inches **Fastener Length:** Between 1.381 inches and 1.411 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.265 inches and 0.285 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.340 inches and 0.350 inches **Extended Washer Thickness:** Between 0.054 inches and 0.074 inches **Grip Diameter:** Between 0.1885 inches and 0.1895 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.052 inches and 1.072 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c Material: Steel comp h11

Material Specification:

Ams6485 assn standard single material response

Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

Thread Series Designator:

Unjf

Specification Data:

56878-lwb22 manufacturers standard

NSN 5306-00-138-4310

Shear Bolt - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0