NSN 5306-00-138-6388

Close Tolerance Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-138-6388

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.357 inches and 0.439 inches
Fastener Length:
Between 2.414 inches and 2.434 inches
Head Style:
Dished hexagon
Head Height:
Between 0.189 inches and 0.204 inches
Width Between Flats:
Between 0.553 inches and 0.564 inches
Grip Diameter:
Between 0.3733 inches and 0.3742 inches
Shank Unthreaded Hole Diameter:
0.106 inches first hole and 0.116 inches first hole
Thread Diameter:
0.375 inches
Grip Length:
Between 1.875 inches and 1.891 inches
Thready Qty Per Inch (tpi):
24
Hardness Rating:
36.0 rockwell c and 41.0 rockwell c
Distance From Head Largest Bearing Surface To Shank Hole Center:
2.299 inches first hole and 2.329 inches first hole
Surface Finish:
63.0 microinches grip
Special Features:
W/retaining element on shank
Material:
Steel
Material Specification:
Mil-b-83050 military specification single material response
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unif

Unjt

NSN 5306-00-138-6388

Close Tolerance Bolt - Page 2 of 2



N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A003b0	

Shelf Life:

Mil-std (military Standard):

Mil-b-83050 spec.