

View Online at <https://aerobasegroup.com/nsn/5306-00-140-3981>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.750 inches and 0.937 inches

Fastener Length:

Between 3.631 inches and 3.725 inches

Head Style:

Hexagon

Head Height:

Between 0.195 inches and 0.211 inches

Width Between Flats:

Between 0.489 inches and 0.500 inches

Thread Diameter:

0.312 inches

Grip Length:

Between 2.788 inches and 2.881 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

18

Min. Tensile Strength (psi):

90000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 316 or steel comp 303 or steel comp 303se or steel comp 316l

Material Specification:

Qq-s0763 federal specification 1st material response or qq-s-763 federal specification 2nd material response or qq-s-763 federal specification 3rd material response or qq-s-763 federal specification 4th material response or qq-s-763 federal specification 5th material response or astm a582 assn standard 6th material response or astm a582 assn standard 7th material response or qq-s-763 federal specification 8th material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: