## NSN 5306-00-141-4524

Close Tolerance Bolt - Page 1 of 2





**Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.374 inches and 0.453 inches Fastener Length: Between 0.765 inches and 0.812 inches **Head Style:** Hexagon **Head Height:** Between 0.109 inches and 0.141 inches Width Between Flats: Between 0.365 inches and 0.377 inches Hole Diameter: 0.046 inches **Grip Diameter:** Between 0.1889 inches and 0.1894 inches **Thread Diameter:** 0.190 inches Grip Length: Between 0.359 inches and 0.391 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon flats Surface Finish: 63.0 microinches grip Material: Steel comp 4140 or steel comp 8740 or steel comp 8630 or steel comp 8735 or steel comp 4130 or steel comp 4037 Surface Treatment: Cadmium and chromate Surface Treatment Specification:

1

Qq-p-416, type 2, cl 2 federal specification all treatment responses

## NSN 5306-00-141-4524

Close Tolerance Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

