## NSN 5306-00-142-4235

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-142-4235 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.692 inches and 0.853 inches **Fastener Length:** Between 1.063 inches and 1.093 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.547 inches and 0.567 inches Width Between Flats: Between 0.616 inches and 0.627 inches **Extended Washer Diameter:** Between 0.928 inches and 0.938 inches **Extended Washer Thickness:** Between 0.123 inches and 0.143 inches **Hole Diameter:** 0.055 inches **Grip Diameter:** Between 0.5605 inches and 0.5615 inches **Thread Diameter:** 0.562 inches **Grip Length:** Between 0.240 inches and 0.260 inches **Hole Quantity:** Hole Type: Drilled Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 220000 pounds per square inch **Hardness Rating:** 46.0 rockwell c and 50.0 rockwell c **Hole Configuration Style:** Round longitudinal hole Material: Steel

**Surface Treatment:** 

Cadmium

## NSN 5306-00-142-4235

Shear Bolt - Page 2 of 2



Nas 672 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0