

View Online at <https://aerobasegroup.com/nsn/5306-00-142-4766>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.655 inches and 0.695 inches

Fastener Length:

Between 0.785 inches and 0.805 inches

Head Style:

Double hexagon w/hole

Head Height:

Between 0.320 inches and 0.340 inches

Width Between Flats:

Between 0.304 inches and 0.313 inches

Extended Washer Diameter:

Between 0.428 inches and 0.448 inches

Extended Washer Thickness:

Between 0.060 inches and 0.070 inches

Shoulder Diameter:

0.265 inches first shoulder and 0.267 inches first shoulder

Shoulder Length:

0.110 inches first shoulder and 0.130 inches first shoulder

Hole Diameter:

0.070 inches

Shank Unthreaded Hole Diameter:

0.060 inches first hole and 0.080 inches first hole

Thread Diameter:

0.250 inches

Hole Quantity:

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

28

Hole Configuration Style:

Round longitudinal hole

Distance From Head Largest Bearing Surface To Shank Hole Center:

0.675 inches first hole and 0.695 inches first hole

Shoulder Shape:

Round first shoulder

Material:

Iron alloy 660

Material Specification:

Ams 5735 assn standard single material response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0