## NSN 5306-00-142-4876



Machine Bolt - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5306-00-142-4876 **Thread Direction:** Right-hand Thread Length: Between 0.625 inches and 0.685 inches **Fastener Length:** 2.125 inches **Head Style:** Double hexagon w/hole **Head Height:** 0.260 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** 0.375 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.440 inches and 1.500 inches **Features Provided:** Finished head **Nonstandard Thread Pitch Diameter:** +0.1644 to 0.1667 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 130000 pounds per square inch Hardness Rating: 248.0 brinell standard and 341.0 brinell standard Minimum Yield Strength: 85000 pounds per square inch **Surface Finish:** 63.0 microinches grip

Material:
Iron alloy 660
Material Specification:
Ams 5732 assn standard single material response
Thread Series Designator:
Unf
Shelf Life:
N/a

## NSN 5306-00-142-4876

Machine Bolt - Page 2 of 2



			ıre:

--

Demilitarization:

No

Fiig:

A003b0