

View Online at <https://aerobasegroup.com/nsn/5306-00-142-4944>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.361 inches and 0.385 inches

Fastener Length:

Between 2.770 inches and 2.790 inches

Head Style:

Hexagon

Head Height:

Between 0.271 inches and 0.291 inches

Width Between Flats:

Between 0.741 inches and 0.752 inches

Shoulder Diameter:

Between 0.505 inches and 0.506 inches

Shoulder Length:

Between 2.405 inches and 2.409 inches

Shank Unthreaded Hole Diameter:

0.094 inches first hole and 0.101 inches first hole

Concentric Hole Depth:

Between 2.460 inches and 2.480 inches

Concentric Hole Diameter:

Between 0.370 inches and 0.380 inches

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Hardness Rating:

30.0 rockwell c and 38.0 rockwell c

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.642 inches first hole and 2.656 inches first hole

Material:

Stainless steel

Material Specification:

Ams 5616 assn standard single material response

Style Designator:

Concentric hole unthreaded

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0