

View Online at <https://aerobasegroup.com/nsn/5306-00-143-1376>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.365 inches and 0.385 inches

**Fastener Length:**

Between 0.365 inches and 0.385 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.146 inches and 0.166 inches

**Width Between Flats:**

Between 0.367 inches and 0.376 inches

**Hole Diameter:**

0.047 inches

**Thread Diameter:**

0.190 inches

**Hole Quantity:**

6

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

32

**Hardness Rating:**

65.0 rockwell a and 69.0 rockwell a

**Hole Configuration Style:**

Hexagon longitudinal hole

**Criticality Code Justification:**

Test

**Surface Finish:**

63.0 microinches bearing surface of head

**Material:**

Stainless steel

**Material Specification:**

+8012, fscm 91547 mfr ref single material response

**Precious Material:**

Silver

**Surface Treatment:**

Silver

**Surface Treatment Specification:**

Ams 2410 assn standard single treatment response

**Test Data Document:**

+6808-91547 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0