
NSN 5306-00-143-1394

Machine Bolt - Page 1 of 2





Thread Class: 3a **Thread Direction: Right-hand Thread Length:** Between 1.655 inches and 1.734 inches Fastener Length: Between 1.796 inches and 1.843 inches **Head Style:** Hexagon **Head Height:** Between 0.640 inches and 0.672 inches Width Between Flats: Between 1.802 inches and 1.815 inches Hole Diameter: 0.070 inches **Thread Diameter:** 1.250 inches Grip Length: Between 0.109 inches and 0.141 inches **Hole Quantity:** Hole Type: Drilled **Features Provided:** Finished head Thready Qty Per Inch (tpi): 12 Min. Tensile Strength (psi): 125000 pounds per square inch Hardness Rating: 26.0 rockwell c and 32.0 rockwell c Hole Configuration Style: Hexagon longitudinal hole Material: Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140 **Material Specification:** Mil-b-6812 military specification all material responses Surface Treatment: Cadmium and chromate

Surface Treatment Specification:

1

Qq-+-416, type 2, class 3 federal specification single treatment response

NSN 5306-00-143-1394

Machine Bolt - Page 2 of 2

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-b-6812 spec.

