NSN 5306-00-143-2259

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-143-2259

| Thread Class: |
|--|
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.579 inches |
| Fastener Length: |
| 0.849 inches |
| Head Style: |
| Double hexagon w/hole |
| Head Height: |
| 0.348 inches |
| Width Between Flats: |
| Between 0.367 inches and 0.376 inches |
| Extended Washer Diameter: |
| Between 0.521 inches and 0.531 inches |
| Extended Washer Thickness: |
| 0.082 inches |
| Hole Diameter: |
| 0.055 inches |
| Grip Diameter: |
| Between 0.3110 inches and 0.3120 inches |
| Thread Diameter: |
| 0.312 inches |
| Grip Length: |
| Between 0.240 inches and 0.260 inches |
| Hole Quantity: |
| 4 |
| Hole Type: |
| Drilled |
| Thready Qty Per Inch (tpi): |
| 24 |
| Min. Tensile Strength (psi): |
| 180000 pounds per square inch |
| Hardness Rating: |
| 39.0 rockwell c and 43.0 rockwell c |
| Hole Configuration Style: |
| Round |
| Material: |
| Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4140 or steel comp 6150 |
| Surface Treatment: |

Cadmium and chromate

NSN 5306-00-143-2259

Shear Bolt - Page 2 of 2



Qq-p-416 type 2 cl 3 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A003b0