# NSN 5306-00-143-2259

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-143-2259

Thread	Class:
Inread	Class:

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

0.579 inches

#### Fastener Length:

0.849 inches

#### **Head Style:**

Double hexagon w/hole

**Head Height:** 

0.348 inches

Width Between Flats:

Between 0.367 inches and 0.376 inches

#### **Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

#### **Extended Washer Thickness:**

0.082 inches

Hole Diameter:

0.055 inches

Grip Diameter:

Between 0.3110 inches and 0.3120 inches

### **Thread Diameter:**

0.312 inches

#### Grip Length:

Between 0.240 inches and 0.260 inches

#### **Hole Quantity:**

4

Hole Type:

Drilled

Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

# Hole Configuration Style:

Round

## Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 4140 or steel comp 6150

## Surface Treatment:

Cadmium and chromate

# NSN 5306-00-143-2259

Shear Bolt - Page 2 of 2



## Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

## Thread Series Designator:

Unjf

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

Fiig:

A003b0