NSN 5306-00-143-2284

Machine Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-143-2284 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.616 inches and 0.696 inches **Fastener Length:** Between 0.928 inches and 0.948 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.250 inches and 0.270 inches Width Between Flats: Between 0.243 inches and 0.251 inches **Extended Washer Diameter:** Between 0.365 inches and 0.385 inches **Extended Washer Thickness:** Between 0.040 inches and 0.050 inches **Thread Diameter:** 0.190 inches **Grip Length:** Between 0.252 inches and 0.312 inches **Features Provided:** Finished head Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 125000 pounds per square inch **Hardness Rating:** 26.0 rockwell c and 32.0 rockwell c **Surface Finish:** 63.0 microinches grip Material: Steel comp 8740

Material Specification:

Ams 6322 assn standard single material response

Surface Treatment:

Oxide film

Surface Treatment Specification:

Ams 2485 assn standard single treatment response

Thread Series Designator:

Unjf

NSN 5306-00-143-2284

Machine Bolt - Page 2 of 2



		ife:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0