# NSN 5306-00-143-2286

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-143-2286

## **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

## Thread Length:

Between 0.589 inches and 0.609 inches

#### Fastener Length:

1.849 inches

#### **Head Style:**

Double hexagon w/hole

#### **Head Height:**

0.348 inches

## Width Between Flats:

Between 0.367 inches and 0.376 inches

## **Extended Washer Diameter:**

Between 0.521 inches and 0.531 inches

#### **Extended Washer Thickness:**

0.082 inches

## Grip Diameter:

Between 0.3110 inches and 0.3120 inches

## **Thread Diameter:**

0.312 inches

## Grip Length:

Between 1.240 inches and 1.260 inches

## Thready Qty Per Inch (tpi):

24

## Min. Tensile Strength (psi):

180000 pounds per square inch

## Hardness Rating:

39.0 rockwell c and 43.0 rockwell c

## Material:

Steel comp e4340 or steel comp 4340 or steel comp 8740 or steel comp 6150 or steel comp 4140

#### Surface Treatment:

Cadmium and chromate

## Surface Treatment Specification:

Qq-p-416 type 2 cl 3 federal specification single treatment response

## **Thread Series Designator:**

Unjf

# Shelf Life:

N/a

# Unit Of Measure:

---



# NSN 5306-00-143-2286

Shear Bolt - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

