

View Online at <https://aerobasegroup.com/nsn/5306-00-143-2426>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.921 inches and 1.000 inches

**Fastener Length:**

Between 3.375 inches and 3.422 inches

**Head Style:**

Hexagon

**Head Height:**

Between 0.328 inches and 0.360 inches

**Width Between Flats:**

Between 0.928 inches and 0.940 inches

**Hole Diameter:**

0.070 inches

**Thread Diameter:**

0.625 inches

**Grip Length:**

Between 2.422 inches and 2.454 inches

**Hole Quantity:**

1

**Hole Type:**

Drilled

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

18

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

26.0 rockwell c and 32.0 rockwell c

**Hole Configuration Style:**

Hexagon flats

**Material:**

Steel comp 4037 or steel comp 4130 or steel comp 8630 or steel comp 8735 or steel comp 8740 or steel comp 4140

**Material Specification:**

Mil-b-6812 military specification all material responses

**Surface Treatment:**

Cadmium and chromate

**Surface Treatment Specification:**

Qq-p-416 type 2, cl 3 federal specification all treatment responses

**Thread Series Designator:**

Unf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-b-6812 spec.