

View Online at <https://aerobasegroup.com/nsn/5306-00-143-2781>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.394 inches and 0.461 inches

**Fastener Length:**

Between 1.966 inches and 2.013 inches

**Head Style:**

Double hexagon

**Head Height:**

Between 0.200 inches and 0.220 inches

**Width Between Flats:**

Between 0.553 inches and 0.564 inches

**Grip Diameter:**

Between 0.3733 inches and 0.3742 inches

**Shank Unthreaded Hole Diameter:**

0.106 inches first hole

**Thread Diameter:**

0.375 inches

**Grip Length:**

Between 1.552 inches and 1.572 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

260000 pounds per square inch

**Hardness Rating:**

51.0 rockwell c and 54.0 rockwell c

**Distance From Head Largest Bearing Surface To Shank Hole Center:**

1.838 inches and 1.858 inches first hole

**Material:**

Steel comp h11

**Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

**Surface Treatment:**

Nickel and cadmium

**Surface Treatment Specification:**

Ams 2416 assn standard all treatment responses

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0