## NSN 5306-00-143-2809

Shear Bolt - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5306-00-143-2809



## **Thread Class:** 3a **Thread Direction: Right-hand Thread Length:** Between 0.387 inches and 0.437 inches Fastener Length: Between 0.709 inches and 0.739 inches **Head Style:** Double hexagon w/hole **Head Height:** Between 0.290 inches and 0.310 inches Width Between Flats: Between 0.304 inches and 0.313 inches **Extended Washer Diameter:** Between 0.428 inches and 0.438 inches **Extended Washer Thickness:** Between 0.059 inches and 0.079 inches Hole Diameter: 0.037 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Thread Diameter:** 0.250 inches Grip Length: Between 0.302 inches and 0.322 inches **Hole Quantity:** 4 Hole Type: Drilled Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 220000 pounds per square inch Hardness Rating: 46.0 rockwell c and 50.0 rockwell c Hole Configuration Style: Round Material: Steel comp h11 **Material Specification:**

Ams 6485 assn standard single material response or ams6487 assn standard single material response

## NSN 5306-00-143-2809

Shear Bolt - Page 2 of 2



Surface Treatment:

Cadmium

Surface Treatment Specification:

Nas 672 assn standard single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0