NSN 5306-00-144-0304

Internal Wrenching Bolt - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5306-00-144-0304

3a Thread Direction: Righ-hand Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.900 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Vidth Across Flats: 0.139 inches Thread Vig Per Inch (tpi): 32 Material: Stel comp 303 Surface Treatment: Passivate Thread Series Designator: Inc Material: Na Unit Of Messure: Inc Information: Inc First Diameter: Inc Interder Inter: Interder Inter: Inter Inter:<	3a Thread Direction: Right-hand Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.238 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Vidth Across Flats: 0.109 inches Thread Vity Per Inch (tpi): 32 Material: Stel comp 303 Surface Treatment: Passivate Thread Series Designator: Inc Shell the: Na Unit of Measure:	Thread Class:	
Tread Direction: Right-hand Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shef Life: Na Unit Of Measure: - Penillitarization: Na Shef Life: Na Denillitarization:	Tread Direction: Right-hand Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.236 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Oty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shef Life: Na Unit Of Measure: - Penilitarization: Na Shef Life: Na Dind Measure: -		
Tread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.226 inches Head Height: 0.226 inches Head Height: 0.226 inches Head Height: 0.226 inches Head Notes Head Notes Head Notes First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.090 inches and 0.436 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Qty Per Inch (tpl): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Unt Of Measure: - - Pemilitarization: No	Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.398 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Midth Across Flats: 0.139 inches Thread Diameter: 0.139 inches Midth Across Flats: 0.109 inches Thread Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Unt Of Measure: - - Demilitarization: No	Thread Direction:	
Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.398 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.139 inches Thread Diameter: 0.139 inches Thread Vay Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Unt Of Measure: - -	Thread Length: Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.398 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.139 inches Thread Vier Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: Na Unt Of Measure: - - Demilitarization: No		
Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Stats: Stel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Uni Of Measure: Demilitarization: No Fig:	Between 0.210 inches and 0.230 inches Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Y Per Inch (tpi): 32 Material: Stel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	-	
Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Material: Stele comp 303 Surface Treatment: Passivate Dread Series Designator: Unc Shelf Life: Na Dint Of Measure: - Penilitarization: No Fig:	Fastener Length: Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Material: Stele comp 303 Surface Treatment: Passivate Dread Series Designator: Unc Shelf Life: Na Dint Of Measure: - Penilitarization: No Fig:		
Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Vity Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.615 inches and 0.645 inches Head Diameter: 0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Vity Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Fastener Length:	
0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Quy Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.226 inches Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Quy Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:		
Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.199 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Height: 0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.199 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Head Diameter:	
0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Yer Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.138 inches First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thread Yer Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.226 inches	
First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	First Diameter From Head: Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Dint Of Measure: Demilitarization: No Fig:	Head Height:	
Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.138 inches	
Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No	Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No	First Diameter From Head:	
Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Between 0.385 inches and 0.435 inches Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Between 0.090 inches and 0.100 inches	
Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: N/a Unt Of Measure: Demilitarization: No Fig:	Internal Drive Style: Hexagon Thread Diameter: 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Sheff Life: N/a Unt Of Measure: Demilitarization: No Fig:	Distance From Largest Bearing Surface Of Head To End Of First Diameter:	
Hexagon Thread Diameter: O.138 inches Width Across Flats: O.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Hexagon Thread Diameter: O.138 inches Width Across Flats: O.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unt Of Measure: Demilitarization: No Fig:	Between 0.385 inches and 0.435 inches	
Thread Diameter: 0.138 inches 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Diameter: 0.138 inches 0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	nternal Drive Style:	
0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.138 inches Width Across Flats: 0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Hexagon	
Width Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Material:Steel comp 303Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Width Across Flats:0.109 inchesThready Qty Per Inch (tpi):32Material:Steel comp 303Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Thread Diameter:	
0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Dint Of Measure: Demilitarization: No Fig:	0.109 inches Thready Qty Per Inch (tpi): 32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unc Dint Of Measure: Demilitarization: No Fig:	0.138 inches	
Thready Qty Per Inch (tpi): 32 34 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thready Qty Per Inch (tpi): 32 34 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Width Across Flats:	
32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32 Material: Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.109 inches	
Material:Steel comp 303Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Material:Steel comp 303Surface Treatment:PassivateThread Series Designator:UncShelf Life:N/aUnit Of Measure:Demilitarization:NoFig:	Thready Qty Per Inch (tpi):	
Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Steel comp 303 Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	32	
Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment: Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Material:	
Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Passivate Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Steel comp 303	
Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Surface Treatment:	
Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:		
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Fiig:	N/a Unit Of Measure: Demilitarization: No Fiig:		
Unit Of Measure: Demilitarization: No Fiig:	Unit Of Measure: Demilitarization: No Fiig:		
 Demilitarization: No Fiig:	 Demilitarization: No Fiig:		
Demilitarization: No Fiig:	Demilitarization: No Fiig:	Jnit Of Measure:	
No Fiig:	No Fiig:		
Fiig:	Fiig:		
	A003b0		