## NSN 5306-00-146-2680

Shear Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-146-2680

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
1.479 inches
Fastener Length:
Between 6.614 inches and 6.634 inches
Head Style:
Double hexagon extended washer
Head Height:
Between 0.913 inches and 0.933 inches
Width Between Flats:
Between 1.052 inches and 1.072 inches
Extended Washer Diameter:
Between 1.615 inches and 1.625 inches
Extended Washer Thickness:
Between 0.212 inches and 0.232 inches
Grip Diameter:
Between 0.998 inches and 0.999 inches
Thread Diameter:
1.000 inches
Grip Length:
Between 5.115 inches and 5.135 inches
Thready Qty Per Inch (tpi):
12
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
39.0 rockwell c and 43.0 rockwell c
Surface Finish:
32.0 microinches grip
Material:
Steel comp 4140 or steel comp e4340 or steel comp 8740 or steel comp 6150
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416, type 2, cl 2 federal specification all treatment responses
Thread Series Designator:
Unjf
Shelf Life:
N/a

N/a

## NSN 5306-00-146-2680

Shear Bolt - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0