

View Online at <https://aerobasegroup.com/nsn/5306-00-146-7371>

Thread Direction:

Right-hand

Thread Length:

0.812 inches

Fastener Length:

2.438 inches

Head Diameter:

0.687 inches

Head Height:

0.250 inches

First Diameter From Head:

Between 0.430 inches and 0.436 inches

Second Diameter From Head:

Between 0.4315 inches and 0.4379 inches

Third Diameter From Head:

Between 0.430 inches and 0.432 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

0.187 inches

Distance From Largest Bearing Surface Of Head To End Of Second Diameter:

1.062 inches

Distance From Largest Bearing Surface Of Head To End Of Third Diameter:

1.625 inches

Thread Diameter:

0.438 inches

Nonstandard Thread Pitch Diameter:

+0.4034 to 0.4050 inches

Thready Qty Per Inch (tpi):

20

Hardness Rating:

33.0 shore scleroscope and 38.0 rockwell superficial 15-n

Externally Relieved Body Diameter Quantity:

3

Special Features:

Axially drilled hole in threaded end 0.125 in. Diameter by 0.187 in. Deep, shank flatted 0.750 in. Lg by 0.417 in. Min 0.418 in. W across flat

Material:

Steel comp 3135

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0