## NSN 5306-00-147-1994

Externally Relieved Body Bolt - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5306-00-147-1994 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.460 inches and 0.520 inches **Fastener Length:** 1.060 inches **Head Style:** Hexagon **Head Height:** 0.188 inches Width Between Flats: Between 0.554 inches and 0.563 inches **First Diameter From Head:** Between 0.369 inches and 0.375 inches **Second Diameter From Head:** Between 0.285 inches and 0.289 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.160 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.540 inches and 0.600 inches **Thread Diameter:** 0.375 inches Thready Qty Per Inch (tpi): 24 Hardness Rating: 26.0 rockwell c and 32.0 rockwell c **Externally Relieved Body Diameter Quantity:** 2 Material: Steel comp 8740 or steel comp 4140 **Surface Treatment:** Cadmium **Surface Treatment Specification:** Ams 2400 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5306-00-147-1994

Externally Relieved Body Bolt - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0